



DESIGN FEATURES

TamlynWrap® Elite WRB is a residential grade moisture management product. This innovative product combines a non-woven backing with a durable coating to offer a balance of strength, moisture resistance, air infiltration protection and vapor permeability. This non-perforated Water Resistive Barrier (WRB) is an economical option providing excellent moisture protection as well as wind and tear resistance.

The ideal vapor permeability facilitates drying of unwanted moisture, may be used in all climate zones and is suitable for use behind all cladding systems. TamlynWrap® Elite meets or exceeds all residential code requirements at an affordable price.

VAPOR PERMEABLE (perm rating of 20)

The vapor permeability facilitates drying of wall components and mitigates potential moisture accumulation as well as the damaging effects of mold and rot.

MEETS ALL EXISTING CODE REQUIREMENTS

Meets and exceeds the ICC acceptance criteria requirements for water resistive barriers (AC38).

BEST PRACTICE

TamlynWrap® Elite WRB must be installed SHINGLE FASHION and integrated with other wall components to promote positive mechanical drainage. All horizontal and vertical overlaps shall be 6" with 12" vertical overlap at any corners. Cap fasteners must be used for attachment per installation guidelines.

ITEM ID	TWE9X125
WIDTH	9 ft
LENGTH	125 ft
COVERAGE	1125 sf
ROLL WEIGHT	22 lbs
VAPOR PERMEANCE	20 perms
THICKNESS	0.3 mm
UV RATING	Maximum 120 days
FIRE RATING	Class A