

Tamlyn® XtremeFlashing™ Tape
XTREMEFLASHING™ TAPE ASPHALT

Tech Support / Sales: 800-334-1676
www.tamlyn.com

XtremeFlashing™ Tape (Asphalt)

FEATURES

XtremeFlashing™ is a self-adhering, self-sealing waterproofing tape designed for use around windows, doors, building seams and in general construction. It is composed of a polymer film that is coated with an aggressive Broad Temperature Spectrum (BTS™) asphalt adhesive. A release liner protects the adhesive and is removed as the tape is installed. The BTS™ adhesive self-seals around punctures caused by nails and staples.

Provides a water tight seal that integrates with other wall components for water management around windows, doors and other wall penetrations such as pipes, electrical conduits, through wall flashing and other flashing details. Must be installed SHINGLE FASHION for proper moisture management.

BENEFITS

- Self-seals around fasteners including nails, staples and screws.
- Protects against water, air, insect and noise infiltration.
- Integrates with other wall components.
- Rubberized asphalt adhesive won't crack or dry.
- Uniform thickness.
- Compatible with most common building materials.
- Available in 4", 6", 9" and 12" wide rolls.

WARRANTY

15 Year Limited Warranty, contact Tamlyn for warranty details and limitations or visit www.tamlyn.com

TECHNICAL SPECIFICATIONS

PROPERTY	Test Method	*Test Results
Material Thickness	ASTM D 3767	25 Mils Nom.
Pliability	AAMA 711	Pass
Vapor Permeance	ASTM E 96	0.008 MAX
Nail Sealability	AAMA 711	Pass
Tensile MD	AAMA 711	≥ 143 psi
Tensile CMD	AAMA 711	≥ 143 psi
Application Temperature		> 35F
UV Exposure Limit		30 Days

Complies with:

AAMA 711-07
ICC-ES AC148, Report ESR 2783

*Based on testing averages.

